

FREE

MATERIAL LIST FOR THE MILAN, SHED PLAN # 1217, 10X8 SIZE

<http://www.just-sheds.com/1215-Milan-Shed-Plan.htm>

Click on or cut and paste the above ULR into your browser to get more information on windows, doors and floor load ratings etc., or material lists for other size Milan shed plans.

Shown below with the door in the front is a 6X8 Milan shed plan.



AVAILABLE IN THIS SERIES

| PLAN # | SIZE |
|--------|------|
| 1215 | 6X8 |
| 1216 | 8X8 |
| 1217 | 10X8 |

PLANS FOR THIS SHED ALLOW YOU TO BUILD ON A CONCRETE SLAB, A WOODEN FLOOR SUPPORTED BY CONCRETE PIERS, OR A WOODEN FLOOR SUPPORTED ON SKIDS. SEE OUR FREE ON LINE ILLUSTRATED CONSTRUCTION GUIDE FOR MORE DETAILS

NOTE: THE FIRST NUMBER STATED IN THE SIZE COLUMN IS ALWAYS THE FRONT. SEE OUR WEB SITE FOR MORE DETAILS.

Discover what we will help you build.



just sheds inc.
www.just-sheds.com

FOR MORE DETAILS SEE THE GLOSSARY OF CONSTRUCTION TERMS IN OUR

[FREE CONSTRUCTION GUIDE](#)

| NO | QUAN | SIZE | DESCRIPTION AND USE | NOTES | COST |
|----|--------|---------------|---|---------|------|
| 1 | 2 | 6" X 6" X 10' | Cedar or pressure treated wood (USE ONLY FOR SKID FOUNDATION) | 1,2,3 | |
| 2 | 8 | 2"X 6"X 16' | Solid bridging, floor and header joists (USE ONLY FOR SKID FOUNDATION) | 1,2,7,3 | |
| 3 | 4 | 3"X 3" | Steel saddle anchors (or 9 anchor bolts if concrete pad is used) | | |
| 4 | 6 | 2"X 8"X 10' | 3-pc built up beam at the front and back | 1,2,7,3 | |
| 5 | 11 | 2"X 8"X 8' | Single and double floor joist as shown on the plans | 2,7,3 | |
| 6 | 14 | 2"X 8" | Single joist hangers (install before plywood) | 7 | |
| 7 | 3 | 4'X 8' X 5/8" | Tongue and groove plywood | 7 | |
| 8 | 9 | 2"X 4"X 16' | When cut will give 1 bottom and 2 top plates for all walls plus misc. needs | 1,3 | |
| 9 | 20 | 2"X 4"X 14' | When cut will give the needed studs of various lengths | 1,3,5 | |
| 10 | 9 | 4'X 8"X 7/16" | Aspenite wall sheeting | | |
| 11 | 4 | 2"X 5"X 12' | Fascia boards all around | 3,4 | |
| 12 | 9 | 2"X 4"X 10' | Roof rafters | | |
| 13 | 4 | 4'X 8"X 3/8" | Spruce plywood roof sheeting | | |
| 14 | 24 | 3/8" | H clips or use scrap wood to support roof sheeting edges | | |
| 15 | 110 | Sq. ft. | Asphalt roof shingles (includes starter strip) | | |
| 16 | 11 | Linear ft. | Metal cap flashing | | |
| 17 | 1 | | Andersen window "NARROLINE" # 20210 | 6 | |
| 18 | 1 | | Therma-tru door # CS210 (outswing is another option) | 6 | |
| 19 | 1 | | Locking door knob (check with door supplier regarding size, set back etc.) | | |
| 20 | 12 | 4'X 8"X 7/16" | Aspenite sheeting for interior walls and ceiling | | |
| 21 | 12 lbs | 3 1/4" | Ardox or spiral framing nails | 5 | |
| 22 | 12 lbs | 2" | Ardox or spiral framing nails | 5 | |
| 23 | 9 lbs | 1 1/4" | Roofing nails; use for shingles, asphalt paper, vinyl siding and trim | 5 | |
| 24 | 300 | Sq. ft. | # 15 asphalt paper | | |
| 25 | 36 | Linear ft. | Vinyl siding starter strip | | |
| 26 | 4 | 3/4"X 3"X 10' | Vinyl siding outside corner post | | |

| | | | | | |
|----|-----|------------|---|---------------|--|
| 27 | 30 | Linear ft. | J channel | | |
| 28 | 40 | Linear ft. | F channel (wall mounted to hold soffit material) | | |
| 29 | 22 | Sq. ft. | Vented soffit | | |
| 30 | 44 | Linear ft. | Under sill trim; use under window and on the top edge of the vinyl fascia | | |
| 31 | 44 | Linear ft. | 6" vinyl fascia | | |
| 32 | 6 | Linear ft. | Vinyl door and window cap | | |
| 33 | 270 | Sq. ft. | Vertical vinyl siding | | |
| 34 | | | Misc. caulking and paint for the door | | |
| 35 | | | | | |
| 36 | | | | | |
| 37 | | | | | |
| 38 | | | | | |
| 39 | | | | | |
| 40 | | | | | |
| | | | | TOTALS | |

Pride will result when adding labor to the above.

NOTE: PLEASE READ ALL NOTES AND SPECIFICATIONS BEFORE ORDERING ANY MATERIALS OR BUILDING

- 1 When cut in two or to the required size one piece will yield the needed amount.
- 2 Cedar or pressure treated wood is recommended. Use cut end treatment if treated wood is used.
- 3 Grade numbers 1 and 2 spruce is the specified lumber for this project.
- 4 2"X 5" lumber is recommended because it suits the 6" vinyl fascia best.
- 5 Consider ordering a few more of these items or others as it is common to use more because of working style, waste or mistakes.
- 6 Always confirm the size of the unit and the rough stud opening (R.S.O.) from the supplier before ordering or building.
- 7 Delete these items and 18 sq. ft. from no. 35 if you choose to build your shed on a concrete pad.
- 8 Not knowing your site or soil conditions prevents us from estimating any of your concrete needs.
- 9 It is the owner's responsibility to apply for all required permits and to build with the necessary skill and in accordance with all required standards.



Visit our family of web sites to get your free catalog with over one hundred shed plans.



www.just-sheds.com

| |
|----------------------|
| MATERIAL LIST |
| SIZE |
| 10'X8' |
| PLAN |
| 1217 |